

**STC**



**CCD Bar Code Scanner**

---

---

---

# CCD Bar Code Scanner

## Special Features:

- With Fuzzy-Logic, minimize faulty scanning
- Wide Read Window
- Ergonomic In Design
- Read Dense Bar Codes
- Light-Weight In Design
- Flexible Custom Configuration
- 1.7 M Shock-Proof
- Auto Upper/Lower Case
- Low Power Consumption
- Built-In Intelligent Decoder
- Auto-Discriminate Bar Codes



## STC-380/K3 Specification:

### Bar Code Reading

Readable Bar	Standard WPC Codes (EAN, UPC/JAN and add-ons'), Code 39, Code 128, Codabar, China Postage, MTX 2/5, IND 2/5, ISBN, Code 93 (Optional codes: Code 11, MSI/Plessey, Delta, IBM...)
Output Interface	Keyboard Wedge, RS232. (Wand, OCIA optional)
Depth of Field	0-20mm
Width of Window	80mm
Purchase Value	0.3 Minimum

### Electrical

Power Supply	DC5V (+/- 5%)
Operating Power Requirement	140mA
Reading Indicator	Beeper and Red LED

### Optical

Image Sensor	Charged-Coupled Device (CCD) Image Sensor
Light Source	Red LED 660nm
Resolution	0.127mm Minimum
Scan Speed	50 Scans Per Second

### Physical

Body Material	ABS Plastic
Weight	120g Without
Connector	DIN-5P, Mini-6P, Dsub-9P, Dsub-25P

### Environment

Operating Temperature	0-50 Degrees C
Operating Humidity	10-90% RH

Note: Specifications may change without notice

## Sole Distributor:

### Ricom Systems

Rm. 804-5, Nan Yang Plaza, 57 Hung To Rd.,  
Kwun Tong, Kowloon, Hong Kong, SAR, PRC.  
Tel.: (852) 25430033 Fax: (852) 25449250  
Website: <http://www.glink.net.hk/~ricom>  
E-mail: [stc@ricom.com.hk](mailto:stc@ricom.com.hk)

## Dealer: