

# LCD Integrated Touch Screen POS Station



# LCD Integrated Touch Screen POS Station

Touch Screen POS Terminal



	PT-3000	PT-3100	PT-4000	PT-4100
CPU	Pentium 233 MHz		Intel Celeron 300-600MHz+, PIII 500-750MHz+	
Memory	64MB expandable to 128MB		64MB expandable to 512MB	
Flash Memory	DiskOnChip 72MB (optional)		DiskOnChip expandable to 288MB, share with SSD (optional)	
Hard Drive	3.5" IDE hard drive or 2.5" IDE hard drive (optional)		3.5" IDE hard drive or 2.5" IDE hard drive (optional)	
Display Memory	1MB (option 2MB)		Share memory programmable for 2MB - 64MB	
LCD Panel	12.1" TFT (Option:DSTN)	13.3" TFT (Option:DSTN)	12.1" TFT (Option:DSTN)	13.3" TFT (Option:DSTN)
Touch Panel (Spill Proof)	Resistive or Capacitive		Resistive or Capacitive	
Dual Display	NO		Dual independent video output	
LED status Indicators	5 LED for power, HD, KB status		5 LED for power, HD, KB status	
Infrared Keyboard Receiver	YES		YES	
Power Supply	AC 115V/230V external power		AC 115V/230V external power	
I/O Interfaces	4 RS232 ports, 3 external with D9 pin connector with +5VDC & +12VDC 1 Parallel Port 1 Ethernet, 10/100 BASE-T 1 PS/2 KB Port 1 PS/2 Mouse port 1 SVGA 2 Cash Drawer port (24VDC) 2 USB		4 RS232 ports, 3 external with D9 pin connector with +5VDC & +12VDC 1 Parallel Port 1 Ethernet, 10/100 BASE-T 1 PS/2 KB Port 1 PS/2 Mouse port 1 SVGA (CRT support up to 1024x768) 2 Cash Drawer port (24VDC) 4 USB Audio Out	
Options	Magnetic card reader, single/dual/three tracks Barcode card reader Customer Pole Display/Rear Customer Display PCMCIA or FAX/Modem (PC104) Internal floppy drive or CD-ROM		Magnetic card reader, single/dual/three tracks Barcode card reader Customer Pole Display/Rear Customer Display FAX/Modem (PC104) Internal Smart Card Reader Internal floppy drive or CD-ROM	
Operating System	DOS, Windows95/98/Me/NT/2000, OS/2, Unix, Linux			
Safety & EMI	UL, CUL, FCC, CE, VCCI Class A		UL, CUL, FCC, CE, VCCI Class B	
Dimensions	WxDxH: 12.8"x 13.4"x12.4" (325mmx340mmx315mm), Packing Size:18.3"x23.2"x16.3"			
Weight	Net weight: 7.2Kg, Gross weight: 12.8Kg			

## Sole Distributor:

### Ricom Systems

Rm. 804-5, Nanyang Plaza, 57 Hung To Rd.,  
Kwun Tong, Kowloon, Hong Kong, SAR, PRC.  
Tel.: (852) 25430033 Fax: (852) 25449250  
Website: <http://www.glink.net.hk/~ricom>  
E-mail: [stc@ricom.com.hk](mailto:stc@ricom.com.hk)

## Dealer: